

WORKING RANGE: Ø 4" IPS ÷ 14" IPS (125 ÷ 355 mm)

COMPACT 355 L



COMPACT 355 L is a worksite machine for pre-insulated pipes in PE, HDPE, PP, from Ø 4" IPS + 14" IPS (125 + 355 mm). Its small dimensions allow it to operate easily inside a dig, plus:

- the machine has a 2-clamp machine body, to lock the outer coating of the pre-insulated pipe
- its heating plate features the well known Digital Dragon 2.0 high precision thermoregulator
- the electrohydraulic gearcase comes inside a protective box
- the facer has a safety microswitch

STANDARD COMPOSITION

Machine body, electrohydraulic gearcase, facer, heating plate with high precision thermoregulator, milling cutter/heating plate support, tool kit.

ON REQUEST (ACCESSORIES)

- Clamps' inserts from
 - Ø 4" IPS to 12" IPS with 250 mm Master adapters
 - Ø 4" DIPS to 12" DIPS with 250 mm Master adapters
 - Ø 125 to 315 mm with 250 mm Master adapters
- Tool for flange necks.



TECHNICAL FEATURES

Working range	4" IPS + 14" IPS (125 + 355 mm)
Materials	HDPE, PP
Power supply	230 V single phase 50-60 Hz
Max absorbed power	5100 W
Weight body machine	130 lb
Total weight	315 lb
Dimension body machine	18" x 31,1" x 22,8"